CORRECTED VERSION

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 2 October 2003 (02.10.2003)

PCT

(10) International Publication Number WO 2003/080212 A1

- B01D 17/032, (51) International Patent Classification⁷: 17/12
- (21) International Application Number:

PCT/EP2003/003170

- (22) International Filing Date: 24 March 2003 (24.03.2003)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

02252120.7

25 March 2002 (25.03.2002)

- (71) Applicant (for all designated States except CA, US): SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).
- (71) Applicant (for CA only): SHELL CANADA LIMITED [CA/CA]; 400, 4th Avenue S.W., Calgary, Alberta T2P 2H5 (CA).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): PUIK, Eric, Johannes [NL/NL]; Volmerlaan 8, NL-2288 GD Rijswijk (NL).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

tion II


- with international search report
- (48) Date of publication of this corrected version:

21 October 2004

(15) Information about Correction: see PCT Gazette No. 43/2004 of 21 October 2004, Sec-

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND DEVICE FOR SEPARATING A MIXTURE OF FLUIDS



(57) Abstract: A mixture of fluids is separated into at least two phases, one of which has a higher density than the other, passing the mixture through a normally horizontal supply pipe, by creating a stratified flow in the supply pipe, by passing the mixture through an inclined pipe, whilst maintaining a stratified flow in the inclined pipe, by extracting fluid with lower density ("lighter phase") via a first discharge system and fluid with a higher density ("heavier phase") via a second discharge system, wherein the interface between the lighter phase and the heavier phase is monitored in the inclined pipe by a level controller means that varies the flow of the fluid of higher density to keep the interface between set levels. The invention also provides a device for employing this method.